

MUSER LED

LED DOWNLIGHTS



Norms
EN 60598-1 , EN 60598-2-2




Body: Steel sheet.
Finish: Powder coated.
Diffuser: Opal polycarbonate.
Light Source: LED 4000K,
CRI >80, 50.000h life.
Control Gear: LED driver,
220-240VAC-50/60Hz.

DOZ - Opal polycarbonate diffuser

LED	W	Lm	Lm/W	η(%)	AxBxC (mm)	z	Kg	HF	DSI	DALI
	20	2960	82	73	380x380x102	368x368	5,4	90096.L406.E	90096.L406.G	90096.L406.H
	40	5440	87	71	380x380x102	368x368	5,4	90096.L412.E	90096.L412.G	90096.L412.H

COLOUR/FINISH



OPTIONS



Colour temperature
3000K



Connector 3-pole
wieland GST 18i3
male




Connector 5-pole
wieland GST 18i5
male



Connector 5-pole
wieland GST 18i5
DIM male



Emergency unit
3 hours




Emergency unit
1 hour

DETAILS




LED detail




Bracket detail

PHOTOMETRY



DIMENSIONS



TO SPECIFY:

Recessed LED luminaire and integral 2960/5440 lumem light engine with square opal diffuser. LED driver included. For ceiling thicknesses of 1-25mm. Optional 3000K, dimmable versions and 1 or 3 hours emergency available - as Roxo Lighting MUSER LED.