

REBA H

ALUMINIUM PROFILE SYSTEMS

Norms
EN 60598-1 , EN 60598-2-1




Body: Extruded aluminium profile.
Finish: Anodised in natural colour.
Light source: T5 (G5) lamp.
Control Gear: Electronic equipment,
220-240VAC-50/60Hz.


PB - Polished double parabolic louvre | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x21	1191x50x140	4,2	90211.P128.A	90211.P128.C	90211.P128.D
	1x35 + 1x28	1491x50x140	5,2	90211.P135.A	90211.P135.C	90211.P135.D
	1x49 + 1x28	1491x50x140	5,2	90211.P149.A	90211.P149.C	90211.P149.D
	1x54 + 1x39	1191x50x140	4,2	90211.P154.A	90211.P154.C	90211.P154.D
	1x80 + 1x54	1491x50x140	5,2	90211.P180.A	90211.P180.C	90211.P180.D

BLINE™ - Opal polycarbonate diffuser | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x21	1191x50x140	4,2	90046.P128.A	90046.P128.C	90046.P128.D
	1x35 + 1x28	1491x50x140	5,2	90046.P135.A	90046.P135.C	90046.P135.D
	1x49 + 1x28	1491x50x140	5,2	90046.P149.A	90046.P149.C	90046.P149.D
	1x54 + 1x39	1191x50x140	4,2	90046.P154.A	90046.P154.C	90046.P154.D
	1x80 + 1x54	1491x50x140	5,2	90046.P180.A	90046.P180.C	90046.P180.D

DAM - Microprismatic diffuser | 60% (Direct) + 40% (Indirect)

LAMP*	W	AxBxC (mm)	Kg	HF	DSI	DALI
 T5	1x28 + 1x21	1191x50x140	4,2	90201.P128.A	90201.P128.C	90201.P128.D
	1x35 + 1x28	1491x50x140	5,2	90201.P135.A	90201.P135.C	90201.P135.D
	1x49 + 1x28	1491x50x140	5,2	90201.P149.A	90201.P149.C	90201.P149.D
	1x54 + 1x39	1191x50x140	4,2	90201.P154.A	90201.P154.C	90201.P154.D
	1x80 + 1x54	1491x50x140	5,2	90201.P180.A	90201.P180.C	90201.P180.D

COLOUR/FINISH



OPTIONS

Suspension



Suspension Type "I" (x2)

Order code
910401

Current supply cable



1,5 m transparent current cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²
1,5 m transparent current cable 1,5 mm²
3 x 1,5 mm²
5 x 1,5 mm²

Order code

940400
940500
940300
940000



TO SPECIFY:

Suspended direct/indirect T5(G5) luminaire, individually mounted in extruded aluminium profile and anodised in natural colour. Aluminium end caps and PB louvre, BLINE polycarbonate or DAM microprismatic diffuser. Available with HF, DSI or DALI control gear. Optional suspensions and ceiling rose – as Roxo Lighting REBA H.

OPTIONS (CONTINUE)

Ceiling rose



Colour of ceiling rose
 Grey
 White
 Black

Order code

970002
 970000
 970001

DETAILS



Clip-in polycarbonate diffuser



Clip-in aluminium louvre

DIMENSIONS

