

ROFY

DOWNLIGHTS

Norms
EN 60598-1 | EN 60598-2-1



Body: Extruded aluminium.
Finish: Powder coated.
Diffuser: Opal polycarbonate.
Light Source: T5 (G5) or TC-L (2G11) lamp.
Control Gear: Electronic equipment,
220-240VAC-50/60Hz.



DOP - Opal polycarbonate diffuser

LAMP*	W	AxB (mm)	Kg	K1 K3	HF	DSI	DALI
T5	G5 1x21 + 8x14	Ø950x85	13,8	• •	90081.0950.A	90081.0950.G	90081.0950.D
	G5 2x14 + 4x21 + 4x28	Ø1250x85	23,5	• •	90081.1250.A	90081.1250.G	90081.1250.D
TC-L	2G11 2x18	Ø350x85	2,7	- -	90081.0350.A	--	--
	2G11 2x24	Ø450x85	3,7	- -	90081.0450.A	90081.0450.G	90081.0450.D
	2G11 3x36	Ø650x85	7,3	- -	90081.0650.A	90081.0650.G	90081.0650.D

COLOUR/FINISH



OPTIONS

Suspension



Suspension Type "I" (x3)
• Suspension kit for Ø350, Ø450, Ø650 and Ø950mm versions.

Order code
910700

Suspension Type "I" (x4)
• Suspension kit only for Ø1250mm version.

910701

Current supply cable



1,5 m transparent current cable 0,75 mm²
3 x 0,75 mm²
5 x 0,75 mm²
7 x 0,75 mm²

Order code

940400

940500

940600

Ceiling rose



Ceiling rose (x3)
• Ceiling rose for Ø350, Ø450, Ø650 and Ø950mm.

Order code
9705

Ceiling rose (x4)
• Ceiling rose only for Ø1250mm.

9706

Emergency unit



Emergency unit 3 hours
Emergency unit 1 hour


Order code

K3


K1

PHOTOMETRY

ROFY 1x21W + 8x14W DOP
Lamp: 1 x 21W/840 + 8 x 14W/840



DIMENSIONS



TO SPECIFY:

Surface or suspended T5(G5) or Compact fluorescent TC-L (2G11) luminaire with five sizes available (Ø350, Ø450, Ø650, Ø950 and Ø1250mm) and round opal polycarbonate diffuser. Optional white, grey, black, red, yellow, green or blue finish and 1 or 3 hours emergency available – as Roxo Lighting ROFY.