

SLIM



DOWNLIGHTS

Norms
EN 60598-1, EN 60598-2-1




Body: Steel sheet.
Finish: Powder coated.
Light Source: T5 (G5) lamp.
Control Gear: Electronic equipment,
220-240VAC-50/60Hz.


Direct/Indirect

	LAMP*		W	AxBxC (mm)	Kg	HF	DSI	DALI
	T5	G5	1x14	620x69x100	2,2	90013.P114.A	90013.P114.C	90013.P114.D
		G5	1x21	920x69x100	3	90013.P121.A	90013.P121.C	90013.P121.D
		G5	1x24	620x69x100	2,2	90013.P124.A	90013.P124.C	90013.P124.D
		G5	1x28	1220x69x100	4,5	90013.P128.A	90013.P128.C	90013.P128.D
		G5	1x35	1520x69x100	4,9	90013.P135.A	90013.P135.C	90013.P135.D
		G5	1x39	920x69x100	3	90013.P139.A	90013.P139.C	90013.P139.D
		G5	1x49	1520x69x100	4,9	90013.P149.A	90013.P149.C	90013.P149.D
		G5	1x54	1220x69x100	4,5	90013.P154.A	90013.P154.C	90013.P154.D
		G5	1x80	1520x69x100	4,9	90013.P180.A	90013.P180.C	90013.P180.D

COLOUR/FINISH




OPTIONS



Opal polycarbonate diffuser (not available for 54/80W).

Lamps as optional

DIMENSIONS



TO SPECIFY:

Wall mounted direct/indirect architectural luminaire, suitable for T5(G5) lamp. Optional opal polycarbonate diffuser and dimmable versions - as Roxo Lighting SLIM.