

TLP LED

LED VANDAL RESISTANT



Norms
EN 60598-1, EN 60598-2-1

CE IP65 IK10 850°C 230V/50Hz

Body: Steel sheet.

Diffuser: 3mm polycarbonate.

Finish: Powder coated in white matt (RAL9016).

Light source: LED 4000K, CRI >80, 50.000h life.

Control Gear: LED driver, 220-240VAC-50/60Hz.



DOZ - Opal polycarbonate diffuser

LED	W	Lm	AxBxC (mm)	HF	DSI	DALI
	2x22	6000	1350x290x66	90DH.222.2J.F4	90DH.222.2J.J4	90DH.222.2J.E4
	2x27	7500	1650x290x66	90DH.227.2J.F4	90DH.227.2J.J4	90DH.227.2J.E4
	4x10	5920	750x600x66	90DH.410.2J.F4	90DH.410.2J.J4	90DH.410.2J.E4

OPTIONS



Colour temperature
3000K





Emergency unit
3 hours



Emergency unit
1 hour

DIMENSIONS



TO SPECIFY:

Surface mounted LED IP65 sealed luminaire with 6000/7500/5920 lumen light engine.

Aluminium frame with tamperproof screws and opal polycarbonate diffuser designed to resist extreme physical impact (IK10). Optional 1 or 3 hours emergency – as Roxo Lighting TLP LED.