

TTM

WATERPROOF

Norms
EN 60598-1, EN 60598-2-1



Body: Polycarbonate tube and anodised aluminium end caps.
Light Source: T5 (G5) lamps included.
Wiring: Pre-wired 1,5m long H07RN-F cable with plastic cable gland.
Control Gear: Electronic equipment, 220-240VAC-50/60Hz.



TUP - Transparent polycarbonate diffuser

LAMP*	W	Lm/W	η(%)	AxB (mm)	Kg	K1 K3	HF	DSI	DALI
T5	G5 2x14	64	86	Ø105x612	2,9	- -	9LDF214.1H.A4	9LDF214.1H.84	9LDF214.1H.74
	G5 2x24	61	84	Ø105x612	2,9	- -	9LDF224.1H.A4	9LDF224.1H.84	9LDF224.1H.74
	G5 2x28	70	81	Ø105x1212	3,1	• •	9LDF228.1H.A4	9LDF228.1H.84	9LDF228.1H.74
	G5 2x35	73	84	Ø105x1512	3,7	• •	9LDF235.1H.A4	9LDF235.1H.84	9LDF235.1H.74
	G5 2x49	70	86	Ø105x1512	3,7	• •	9LDF249.1H.A4	9LDF249.1H.84	9LDF249.1H.74
	G5 2x54	61	77	Ø105x1212	3,1	• •	9LDF254.1H.A4	9LDF254.1H.84	9LDF254.1H.74

TOP - Opal polycarbonate diffuser

LAMP*	W	Lm/W	η(%)	AxB (mm)	Kg	K1 K3	HF	DSI	DALI
T5	G5 2x14	61	81	Ø105x612	2,9	- -	9LDF214.1G.A4	9LDF214.1G.84	9LDF214.1G.74
	G5 2x24	58	80	Ø105x612	2,9	- -	9LDF224.1G.A4	9LDF224.1G.84	9LDF224.1G.74
	G5 2x28	67	77	Ø105x1212	3,1	• •	9LDF228.1G.A4	9LDF228.1G.84	9LDF228.1G.74
	G5 2x35	68	78	Ø105x1512	3,7	• •	9LDF235.1G.A4	9LDF235.1G.84	9LDF235.1G.74
	G5 2x49	64	79	Ø105x1512	3,7	• •	9LDF249.1G.A4	9LDF249.1G.84	9LDF249.1G.74
	G5 2x54	57	72	Ø105x1212	3,1	• •	9LDF254.1G.A4	9LDF254.1G.84	9LDF254.1G.74

PBP - Polished double parabolic louvre and transparent polycarbonate diffuser

LAMP*	W	Lm/W	η(%)	AxB (mm)	Kg	K1 K3	HF	DSI	DALI
T5	G5 2x14	42	56	Ø105x612	3,1	- -	9LDF214.79.A4	9LDF214.79.84	9LDF214.79.74
	G5 2x24	38	53	Ø105x612	3,1	- -	9LDF224.79.A4	9LDF224.79.84	9LDF224.79.74
	G5 2x28	55	63	Ø105x1212	3,6	• •	9LDF228.79.A4	9LDF228.79.84	9LDF228.79.74
	G5 2x35	58	66	Ø105x1512	4	• •	9LDF235.79.A4	9LDF235.79.84	9LDF235.79.74
	G5 2x49	51	63	Ø105x1512	4	• •	9LDF249.79.A4	9LDF249.79.84	9LDF249.79.74
	G5 2x54	52	66	Ø105x1212	3,6	• •	9LDF254.79.A4	9LDF254.79.84	9LDF254.79.74

OPTIONS



276 IP68 stainless steel end caps (x2)
915100 Basic stainless steel fixing holder (x2)
915101 Wall fixing holder (x2)
915102 Acrylic fixing holder (x2)
910200 Suspension type "I" (x2) (Only for basic stainless steel fixing holder)
K3 Emergency unit 3 hours

DETAILS



Louvre version




K1 Emergency unit 1 hour
925000 Metal cable gland
940200 1,5m current cable 3x1,5mm² for indoor applications
940201 1,5m current cable 5x1,5mm² for indoor applications




PHOTOMETRY


TTM 2x49W TUP
Lamp: 2 x 49W/840 HO




TTM 2x49W TOP
Lamp: 2 x 49W/840 HO



TTM 2x49W PBP
Lamp: 2 x 49W/840 HO



DIMENSIONS



TO SPECIFY:

Waterproof luminaire IP68 in transparent/opal polycarbonate tube or polished high output louvre. Luminaire with 105mm diameter, available with twin 14/24/28/35/49/54W T5(G5) fluorescent lamps. Optional surface, suspended or wall mounted versions, dimmable and 1 or 3 hours emergency available - as Roxo Lighting TTM.